


Fig. 1



APPROVED	O.G. FIG.	
BY	CLASS	SUBCLASS
DRAFTSMAN		

Fig.2




Fig.3

FROM STEP S11 IN FIG.2




Fig.4






Fig.5



APPROVED	O.G. FIG.	
BY	CLASS	SUBCLASS
DRAFTSMAN		


Fig.6



0959710 - 0016000

APPROVED	O.G. FIG.
BY	CLASS SUBCLASS
DRAFTSMAN	

Fig.7



TO STEP S58 IN FIG.8

Fig.8




Fig.9





Fig. 10




APPROVED BY DRAFTSMAN	O.G. FIG.
	CLASS SUBCLASS

Fig. 11

CATEGORY	OUTLINE	DRAWING FUNCTION: OUTLINE TO BE EVALUATED
(1) CURVECAPS	CURVE DRAWING CAPABILITY	CC-CIRCLE
(2) LINECAPS	LINE DRAWING CAPABILITY	LC - POLYSCANLINE
(3)	LINE DRAWING CAPABILITY	GROUP DRAWING OF SCANLINE
(4) POLYGONCAPS	POLYGON DRAWING CAPABILITY	LC - STYLED
(5) POLYGONCAPS	POLYGON DRAWING CAPABILITY	DRAWING OF STYLED LINE
(6) TEXTCAPS	TEXT DRAWING CAPABILITY	PC - RECTANGLE
(7) TEXTCAPS	TEXT DRAWING CAPABILITY	DRAWING OF RECTANGLE
(8) CLIPCAPS	CLIPPING CAPABILITY	PC - WINDPOLYGON
(9) RASTERCAPS	RASTER CAPABILITY	WHOLE-AREA PAINT-OUT
(10) RASTERCAPS	RASTER CAPABILITY	OF POLYGON
		TC - RA - ABLE
		RASTER FONT
		CHARACTER ROTATION BY
		90 DEGREES
		TC - CR - 90
		CLIPPING OF RECTANGLE
		RC - BITBLT
		BIT-MAP TRANSFER
		RC - STRETCHDIB
		STRETCHING/CONTRACTION
		OF DIB(BIT MAP)

APPROVED	O.G. FIG.	
BY	CLASS	SUBCLASS
DRAFTSMAN		

Fig. 12



APPROVED	O.G. FIG.	
BY	CLASS	SUBCLASS
DRAFTSMAN		

Fig. 13




Fig. 14






Fig.15



APPROVED BY DRAFTSMAN	O.G. FIG.
	CLASS SUBCLASS

Fig.16



APPROVED BY	O.G. FIG.	
DRAFTSMAN	CLASS	SUBCLASS

Fig. 17

PDL COMMAND (2 BYTES)	ATTRIBUTE INFORMATION AMOUNT	EVALUATION SIZE	COMMAND OUTLINE	ATTRIBUTE INFORMATION OUTLINE
(1) TEXT		52 BYTES	TEXT	OUTLINE FONT
(2) LINE		14 BYTES	LINE	START-END POINT COORDINATES LINE KIND INFORMATION
(3) CIRCLE		14 BYTES	CIRCLE	LEFT-UPPER-RIGHT-LOWER END COORDINATES CIRCLE KIND INFORMATION
(4) CURVE		18 BYTES	CURVE	
(5) PIXEL	4 BYTES	6 BYTES	PIXEL	COORDINATES
(6) IMAGE	IMAGE DATA	40 KBYTES	BIT MAP	X-DIRECTION SIZE, Y-DIRECTION SIZE
(7) DUMMY	38 BYTES	40 BYTES		OTHER THAN (1) TO (6)

APPROVED	O.G. FIG.	
BY	CLASS	SUBCLASS
DRAFTSMAN		

Fig. 18

